



JUN 04 2010

2010 MAY 11 PM 1:58

56-0067
cook

11117 Mockingbird Drive
Omaha, Nebraska 68137
www.atcassociates.com
Phone: 402.697.9747
Fax: 402.697.9170

April 9, 2010

Tennessee Dept. of Environment & Conservation
Div. of Air Pollution Control
9th Floor, L&C Annex
401 Church Street
Nashville, TN 37243-1531

RE: U.S. Cellular® - Emergency Generator Air Permit Applications

Dear Sir or Madam:

ATC Associates, Inc. was retained by U.S. Cellular® to complete air permit applications for their emergency generators within the State of Tennessee pursuant to APC Rule Ch. 1200. Upon review of U.S. Cellular's databases and through confirmation with their Network Field Engineers, ATC determined that U.S. Cellular currently has fifteen (15) generators within the State of Tennessee that are required to obtain air permits.

Attached are the Air Permit Application Forms (Form APC20, Form APC21&24 and APC22) for the fifteen (15) generators along with a check in the amount of \$1,500.00 (\$100.00/facility) for the permit fees. Also attached is a list of the fifteen (15) facilities with generators.

If you should have any questions, please do not hesitate to call me at (515) 981-3216.

Sincerely,
ATC ASSOCIATES INC.

A handwritten signature in cursive script that reads 'Mike Freese'.

Mike Freese, REM
Sr. Project Manager

Attachments

cc: Doug Zabrin – U.S. Cellular®
Brad Summers – U.S. Cellular®
Dale Mattson – U.S. Cellular®
Jerry Williams – U.S. Cellular®
Mark Clark – U.S. Cellular®
Tony Chandler – U.S. Cellular®

Permit Required Facilities

Site #	Site Name	Site Address	Site City	Site State	Site Zip	Site County	Site Contact	Contact Phone	Gen. Mfr.	Gen. Model	Gen. Size (KW)	Generator Fuel Type
411316	411316 RATTLESNAKE DT	347 Tower Road	Gatlinburg	TN	37738	Sevier	Brad Summers	865.705.7600	Cummins	DGGD	35	DSL - Diesel
860327	860327 HARTSVILLE	136 Morrison Street	Hartsville	TN	37074	Trousdale	Dale Mattson	Not Listed	Kohler	50REOZJC	37	DSL - Diesel
860333	860333 RED BOILING SPRINGS	8101 Heady Ridge Rd.	Red Boiling Springs	TN	37150	Macon	Dale Mattson	Not Listed	Kohler	50REOZJC	37	DSL - Diesel
860338	860338 WESTSIDE	461 Green Grove Rd.	Lafayette	TN	37083	Macon	Dale Mattson	Not Listed	Kohler	50REOZJC	37	DSL - Diesel
860319	860319 PIONEER	8638 Sticking Creek Rd.	Pioneer	TN	37847	Campbell	Jerry Williams	865.679.4446	Kohler	50REOZJC	37	DSL - Diesel
860348	860348 PEAVINE	653 Eroh Rd.	Crossville	TN	38571	Cumberland	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel
860359	860359 ROBBINS	East Robbins Rd.	Robbins	TN	37852	Scott	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel
860362	860362 PINEY	252 Old Harriman Hwy.	Harriman	TN	37748	Roane	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel
860367	860367 CORDELL	8787 James Baker Highway	Huntsville	TN	37756	Scott	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel
860368	860368 MOFFIT	4496 Straight Fork Road	Pioneer	TN	37847	Scott	Mike Clark	931.979.0041	Kohler	30REOZJC	27	DSL - Diesel
860381	860381 STEPHENS	180 Tree Top Lane	Coalfield	TN	37719	Morgan	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel
411346	411346 DOUGLAS DAM	1443 Holbert Road	Dandridge	TN	37725	Sevier	Tony Chandler	865.679.0010	Kohler	50REOZJC	37	DSL - Diesel
860354	860354 CRAB ORCHARD	384 Godsey Road	Crab Orchard	TN	37723	Cumberland	Mike Clark	931.979.0041	Kohler	30REOZJC	27	DSL - Diesel
860358	860358 GLEN MARY	593 Huckelby Road	Robbins	TN	37852	Scott	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel
860345	860345 TANSI	490 Vandiver Rd.	Crossville	TN	38571	Cumberland	Mike Clark	931.979.0041	Kohler	50REOZJC	37	DSL - Diesel

0860	05/06/2010	R 0000199217	1500009260	
INVOICE NUMBER	DATE	AMOUNT	DISCOUNT	NET AMOUNT
050510 AIR PERMIT FEES	05/05/2010	\$1,500.00 2010 MAY 11 PM 1:58		\$1,500.00

Tennessee RSA No. 3 LP
8410 W Bryn Mawr Ave
Suite 700
Chicago, IL 60631-3415

REMOVE DOCUMENT ALONG THIS PERFORATION

Tennessee RSA No. 3 LP
8410 W Bryn Mawr Ave
Suite 700
Chicago, IL 60631-3415



1500009260
BANK OF AMERICA

2-3
710 IL

DATE
May 06, 2010

0860 0000199217

PAY
ONLY \$1,500.00

VOID IF NOT CASHED WITHIN 180 DAYS OF ISSUE

One thousand five hundred and 00/100 Dollars

PAY
TO THE
ORDER
OF

State of Tennessee
Dept of Environment - Conservation
401 Church Street
NASHVILLE TN 37243

John P. Ramsey
Shaybell


⑈ 1500009260 ⑈ ⑆ 071000039⑆ 5800963430 ⑈

Remove this stub before cashing. Fold, crease, and tear along perforation.

1500009260

0860 0000199217

Tennessee RSA No. 3 LP
8410 W Bryn Mawr Ave
Suite 700
Chicago, IL 60631-3415



State of Tennessee
Dept of Environment - Conservation
401 Church Street
NASHVILLE TN 37243

Call 1-800-PICK-UPS® (1-800-742-5877) or visit ups.com®

- For UPS Next Day Air services, there is no weight limit for envelopes containing letters, business correspondence, urgent documents, and electronic media. When a UPS Next Day Air service is selected, UPS Express Envelopes containing items other than those listed above are subject to the corresponding rates for the applicable weight.
- Express Envelopes are not recommended for shipments of electronic media containing sensitive personal information.
- For UPS Worldwide Express, the UPS Express Envelope may be used only for documents of no commercial value. There is no limit on the weight or number of pages you can enclose.
- Do not use UPS 2nd Day Air services to send letters weighing over 13 ounces in this envelope. For UPS 2nd Day Air services, UPS Express Envelopes weighing one pound or more are subject to the corresponding rates for the applicable weight.

Do not seal inside or inside flap.


Reusable Express Envelope

Legal size

Print a paper weight by using the envelope a second time—affix to return to sender or to ship to another recipient. See online instructions on ups.com.

Decision Green™

Decision Green is UPS's environmental platform, reflecting our pursuit of sustainable business practices worldwide. For example, this envelope is made from 100% recycled material and is both reusable and recyclable.



International Shipping Notice — Carriage hereunder may be subject to the rules relating to liability and other terms and/or conditions established by the Convention for the Unification of Certain Rules Relating to International Carriage by Air (the "Warsaw Convention") and/or the Convention on the Contract for the International Carriage of Goods by Road (the "CMR Convention"). These commodities, technology or software were exported from the U.S. in accordance with the Export Administration Regulations. Diversion to U.S. is prohibited.

ENTRANCE GOODWIN 7720 S. WILSON US CELLULAR CORPORATION 8410 W. BRYN MAWR AVENUE CHICAGO, IL 60631		2 LBS	1 OF 1
SHIP TO: TENNESSEE DEPT. OF ENVIRONMENTAL DIV. OF AIR POLLUTION CONTROL 9TH FLOOR L&C ANNEX 401 CHURCH ST. NASHVILLE TN 37219-2310			
		TN 371 9-02	
UPS 2ND DAY AIR		2	
TRACKING #: 1Z 61X 045 02 9859 4810			
BILLING: P/P			
Cost Center: 175105		US 12 026 NOV2000 0104 04/2010	

UPS CampusShip: Lat

Envelope is for use
in following services:

DIV OF AIR POLLUTION CONTROL
401 CHURCH ST
NASHVILLE TN 37219-2310

P. WHITE S. BR2
KROB - 8010
1Z61K045029859 4810

Envelope for:
KROB

100% Recycled Fiber
80% Post-Consumer



NOT TO BE USED FOR TITLE V APPLICATIONS

2010 MAY 11 PM 1:59

PERMIT APPLICATION

APC 20

PLEASE TYPE OR PRINT AND SUBMIT IN DUPLICATE FOR EACH EMISSION SOURCE. ATTACH APPROPRIATE SOURCE DESCRIPTION FORMS.

1. ORGANIZATION'S LEGAL NAME			/// FOR	APC COMPANY--POINT NO.
US Cellular				510-0067
2. MAILING ADDRESS (ST/RD/P.O. BOX)			/// APC	APC LOG/PERMIT NO.
8410 W. Bryn Mawr Avenue, Suite 900				63692
CITY	STATE	ZIP CODE	PHONE WITH AREA CODE	
Chicago	Illinois	60631	773-399-6899	
3. PRINCIPAL TECHNICAL CONTACT			PHONE WITH AREA CODE	
John Glatz/US Cellular Mike Freese/ATC Associates			773-399-6899 515-981-3216	
4. SITE ADDRESS (ST/RD/HWY)			COUNTY NAME	
461 Green Grove Road (Site known as 860338 Westside)			Macon	
CITY OR DISTANCE TO NEAREST TOWN		ZIP CODE	PHONE WITH AREA CODE	
Westmoreland		37083	931-979-2499 Dale Mattson - Network Field Eng.	
5. EMISSION SOURCE NO. (NUMBER WHICH UNIQUELY IDENTIFIES THIS SOURCE)		PERMIT RENEWAL		
ES-1		YES () NO (X)		
6. BRIEF DESCRIPTION OF EMISSION SOURCE				
Backup Emergency Generator (Kohler Model 50REOZJC)				

7. TYPE OF PERMIT REQUESTED				
CONSTRUCTION	STARTING DATE	COMPLETION DATE	LAST PERMIT NUMBER	EMISSION SOURCE REFERENCE NUMBER
(X)	Installed 10/09			
OPERATING	DATE CONSTRUCTION STARTED	DATE COMPLETED	LAST PERMIT NUMBER	EMISSION SOURCE REFERENCE NUMBER
(X)	Installed 10/09			
LOCATION TRANSFER	TRANSFER DATE		LAST PERMIT NUMBER	EMISSION SOURCE REFERENCE NUMBER
()				
ADDRESS OF LAST LOCATION				

8. DESCRIBE CHANGES THAT HAVE BEEN MADE TO THIS EQUIPMENT OR OPERATION SINCE THE LAST CONSTRUCTION OR OPERATING PERMIT APPLICATION.

9. SIGNATURE (APPLICATION MUST BE SIGNED BEFORE IT WILL BE PROCESSED)		DATE
		4/30/10
10. SIGNER'S NAME (TYPE OR PRINT)	TITLE	PHONE WITH AREA CODE
John Glatz	Director Real Estate Services	773-399-6899



NOT TO BE USED FOR TITLE V APPLICATIONS

2010 MAY 11 PM 1:59

PROCESS OR FUEL BURNING SOURCE DESCRIPTION

APC21(& 24)

PLEASE TYPE OR PRINT, SUBMIT IN DUPLICATE AND ATTACH TO THE PERMIT APPLICATION.

1. ORGANIZATION NAME US Cellular		/// FOR	APC COMPANY-POINT NO.
2. EMISSION SOURCE NO. (AS ON PERMIT APPLICATION) ES-1	SIC CODE 4812	/// APC	APC PERMIT/LOG NO.

3. DESCRIPTION OF PROCESS OR FUEL BURNING UNIT

Backup Emergency Generator (Kohler Model 50REOZJC)

4. NORMAL OPERATION: → Emergency generator is exercised on a periodic basis	HOURS/DAY	DAYS/WEEK	WEEKS/YEAR	DAYS/YEAR
5. PERCENT ANNUAL THROUGHPUT: →	DEC.-FEB. 25%	MARCH-MAY 25%	JUNE-AUG. 25%	SEPT.-NOV. 25%

6. TYPE OF PERMIT APPLICATION

(CHECK BELOW ONE ONLY)

PROCESS SOURCE: APPLY FOR A SEPARATE PERMIT FOR EACH SOURCE. (CHECK AT RIGHT, AND COMPLETE LINES 7, 8, 13, AND 14).

()

PROCESS SOURCE WITH IN-PROCESS FUEL: PRODUCTS OF COMBUSTION CONTACT MATERIALS HEATED. APPLY FOR A SEPARATE PERMIT FOR EACH SOURCE. (CHECK AT RIGHT, AND COMPLETE LINES 7, 8, AND 10 THROUGH 14)

()

NON-PROCESS FUEL BURNING SOURCE: PRODUCTS OF COMBUSTION DO NOT CONTACT MATERIALS HEATED. COMPLETE THIS FORM FOR EACH BOILER OR FUEL BURNER AND COMPLETE AN EMISSION POINT DESCRIPTION FORM (APC 22) FOR EACH STACK. (CHECK AT RIGHT, AND COMPLETE LINES 9 TO 14)

(X)

7. TYPE OF OPERATION: CONTINUOUS,

BATCH

NORMAL BATCH
TIME

NORMAL BATCHES/DAY

()

()

8. PROCESS MATERIAL INPUTS AND IN-PROCESS SOLID FUELS

DIAGRAM*
REFERENCE

INPUT RATES (POUNDS/HOUR)

DESIGN ACTUAL

/(
/ (FOR APC USE ONLY)
/ SCC CODE

A.

B.

C.

D.

E.

F.

G.

TOTALS

* A SIMPLE PROCESS FLOW DIAGRAM MUST BE ATTACHED.

(OVER)

9. BOILER OR BURNER DATA: (COMPLETE LINES 9 TO 14 USING A SEPARATE FORM FOR EACH BOILER)

BOILER NUMBER	STACK NUMBER**	TYPE OF FIRING***	RATED BOILER HORSEPOWER	RATED INPUT CAPACITY (10 ⁶ BTU/HR)	OTHER BOILER RATING (SPECIFY CAPACITY AND UNITS)
ES-1	EP-1				37 kilowatt
BOILER SERIAL NO.		DATE CONSTRUCTED	DATE OF LAST MODIFICATION (EXPLAIN IN COMMENTS BELOW).		
2257226		October 2009	NA		

** BOILERS WITH A COMMON STACK WILL HAVE THE SAME STACK NUMBER.

*** CYCLONE, SPREADER (WITH OR WITHOUT REINJECTION), PULVERIZED (WET OR DRY BOTTOM, WITH OR WITHOUT REINJECTION), OTHER STOKER (SPECIFY TYPE), HAND FIRED, AUTOMATIC, OR OTHER TYPE (DESCRIBE BELOW IN COMMENTS).


10. FUEL DATA: (COMPLETE FOR A PROCESS SOURCE WITH IN-PROCESS FUEL OR A NON-PROCESS FUEL BURNING SOURCE)

PRIMARY FUEL TYPE (SPECIFY)				STANDBY FUEL TYPE(S) (SPECIFY)				
Diesel Fuel								
FUELS USED	ANNUAL USAGE	HOURLY USAGE		% SULFUR	% ASH	BTU VALUE OF FUEL		(FOR APC ONLY) SCC CODE
		DESIGN	AVERAGE					
NATURAL GAS:	10 ⁶ CUFT	CUFT	CUFT	/ / / /	/ /			
				/ / / /	/			
					/ /			
#2 FUEL OIL: Diesel Fuel	10 ³ GAL <100 gal./year	GAL: 4.3 gal./hr. @ full standby	GAL: 3.6 gal./hr. @ full prime	<0.5%	/ /	140,000/gal.		20200102
					/			
					/ /			
#5 FUEL OIL:	10 ³ GAL	GAL	GAL		/ /			
					/			
					/ /			
#6 FUEL OIL:	10 ³ GAL	GAL	GAL		/ /			
					/			
					/ /			
COAL:	TONS	LBS	LBS					
WOOD:	TONS	LBS	LBS	/ / / /	/ /			
				/ / / /	/			
					/ /			
LIQUID PROPANE:	10 ³ GAL	GAL	GAL	/ / / /	/ /			
				/ / / /	/			
					/ /			
OTHER (SPECIFY TYPE & UNITS.):								

11. IF WOOD IS USED AS A FUEL, SPECIFY TYPES AND ESTIMATE PERCENT BY WEIGHT OF BARK

12. IF WOOD IS USED WITH OTHER FUELS, SPECIFY PERCENT BY WEIGHT OF WOOD CHARGED TO THE BURNER.

13. COMMENTS: Process Flow Diagram below.



14. SIGNATURE

DATE

4/30/2010



NOT TO BE USED FOR TITLE V APPLICATIONS

2010 MAY 11 PM 1:59

EMISSION POINT DESCRIPTION

APC 22

PLEASE TYPE OR PRINT AND SUBMIT IN DUPLICATE FOR EACH STACK OR EMISSION POINT.
ATTACH TO THE PERMIT APPLICATION.

1. ORGANIZATION NAME US Cellular				///	APC COMPANY POINT NO.
2. EMISSION SOURCE NO. (FROM APPLICATION) ES-1				FOR	APC SEQUENCE NO.
3. LOCATION: →				APC	
LATITUDE	LONGITUDE	UTM VERTICAL		UTM HORIZONTAL	
36.520515	-86.175815				
4. BRIEF EMISSION POINT DESCRIPTION (ATTACH A SKETCH IF APPROPRIATE): Exhaust for emergency generator					DISTANCE TO NEAREST PROPERTY LINE (FT) Remote Cell location >50 ft.


COMPLETE LINES 5 AND 6 IF DIFFERENT FROM THAT ON THE PROCESS OR FUEL BURNING SOURCE DESCRIPTION (APC 21)

5. NORMAL OPERATION: →	HOURS/DAY Emergency generator is exercised on a periodic	DAYS/WEEK	WEEK/YEAR	DAYS/YEAR		
6. PERCENT ANNUAL THROUGHPUT: →	DEC.-FEB. 25%	MARCH-MAY 25%	JUNE-AUG. 25%	SEPT.-NOV. 25%		
7. STACK OR EMISSION POINT DATA: →	HEIGHT ABOVE GRADE (FT) ~5'	DIAMETER (FT) 0.2	TEMPERATURE (°F) 1066	% OF TIME OVER 125°F	DIRECTION OF EXIT (UP, DOWN OR HORIZONTAL) Vertical	
DATA AT EXIT CONDITIONS: →	FLOW (ACTUAL FT ³ /MIN.) 456	VELOCITY (FT/SEC)	MOISTURE (GRAINS/FT ³)		MOISTURE (PERCENT)	
DATA AT STANDARD CONDITIONS: →	FLOW (DRY STD. FT ³ /MIN) 423	VELOCITY (FT/SEC)	MOISTURE (GRAINS/FT ³)		MOISTURE (PERCENT)	
8. AIR CONTAMINANTS	ACTUAL EMISSIONS			EMISSIONS* EST. METHOD	CONTROL DEVICES*	CONTROL EFFICIENCY%
	EMISSIONS (LBS/HR) AVERAGE MAXIMUM		CONCENTRATION			
PARTICULATES	0.15	0.18	**	0.05	3	
SULFUR DIOXIDE	0.14	0.17	***	0.04	3	
CARBON MONOXIDE	0.47	0.56	PPM	0.14	3	
ORGANIC COMPOUNDS	0.18	0.21	PPM	0.05	3	
NITROGEN OXIDES	2.17	2.60	PPM	0.65	3	
FLUORIDES				<0.01		
OTHER(SPECIFY)	Above emissions based on full prime	Above emissions based on full standby		Emissions above based on 500hrs/yr and full standby.	Above based on SCC 20200102	

(OVER)

9. CHECK TYPES OF MONITORING AND RECORDING INSTRUMENTS THAT ARE ATTACHED:OPACITY MONITOR (☐), SO2 MONITOR (☐), NOX MONITOR (☐), OTHER (SPECIFY IN COMMENTS) (X ☐)**10. COMMENTS**

Hour meter

11. SIGNATURE**DATE**

4/30/2010

* REFER TO THE BACK OF THE PERMIT APPLICATION FORM FOR ESTIMATION METHOD AND CONTROL DEVICE CODES.

** EXIT GAS PARTICULATE CONCENTRATION UNITS: PROCESS — GRAINS/DRY STANDARD FT3 (70°F); WOOD FIRED BOILERS — GRAINS/DRY STANDARD FT3 (70°F); ALL OTHER BOILERS — LBS/MILLION BTU HEAT INPUT.

*** EXIT GAS SULFUR DIOXIDE CONCENTRATIONS UNITS: PROCESS — PPM BY VOLUME, DRY BASES; BOILERS — LBS/MILLION BTU HEAT INPUT.

Alternator Specifications

Specifications	Alternator
Manufacturer	Kohler
Type	4-Pole, Rotating-Field
Exciter type	Brushless, Permanent-Magnet
Leads: quantity, type	12, Reconnectable
Voltage regulator	Solid State, Volts/Hz
Insulation:	NEMA MG1
Material	Class H
Temperature rise	130°C, Standby
Bearing: quantity, type	1, Sealed
Coupling	Flexible Disc
Amortisseur windings	Full
Voltage regulation, no-load to full-load	
Permanent magnet (PM) alternator	±2% Average
550 controller (with 0.5% drift due to temperature variation)	3-Phase Sensing, ±0.25%
One-step load acceptance	100% of Rating
Unbalanced load capability	100% of Rated Standby Current
Peak motor starting kVA:	(35% dip for voltages below)
480 V 4P7 (12 lead)	194
480 V 4P8 (12 lead)	212
240 V 4Q10 (4 lead)	155

- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting.
- Sustained short-circuit current of up to 300% of the rated current for up to 10 seconds.
- Sustained short-circuit current enabling downstream circuit breakers to trip without collapsing the alternator field.
- Self-ventilated and dripproof construction.
- Vacuum-impregnated windings with fungus-resistant epoxy varnish for dependability and long life.
- Superior voltage waveform from a two-thirds pitch stator and skewed rotor.
- Fast-Response™ II brushless alternator with brushless exciter for excellent load response.

Application Data

Engine

Engine Specifications	
Manufacturer	John Deere
Engine model	4024HF285B
Engine type	4-Cycle, Turbocharged
Cylinder arrangement	4 Inline
Displacement, L (cu. in.)	2.4 (149)
Bore and stroke, mm (in.)	86 x 105 (3.39 x 4.13)
Compression ratio	18.2:1
Piston speed, m/min. (ft./min.)	375 (1230)
Main bearings: quantity, type	5, Replaceable Insert
Rated rpm	1800
Max. power at rated rpm, kWm (BHP)	60 (80)
Cylinder head material	Cast Iron
Crankshaft material	Ductile Iron
Valve material:	
Intake	Chromium-Silicon Steel
Exhaust	Stainless Steel
Governor: type, make/model	JDEC Electronic, Level 18, EUP
Frequency regulation, no-load to full-load	Isochronous
Frequency regulation, steady state	±0.25%
Frequency	Fixed
Air cleaner type, all models	Dry

Exhaust

Exhaust System	
Exhaust manifold type	Dry
Exhaust flow at rated kW, m³/min. (cfm)	12.0 (423)
Exhaust temperature at rated kW, dry exhaust, °C (°F)	574 (1066)
Maximum allowable back pressure, kPa (in. Hg)	7.5 (2.2)
Exhaust outlet size at engine hookup, mm (in.)	63.5 (2.5)

Engine Electrical

Engine Electrical System	
Battery charging alternator:	
Ground (negative/positive)	Negative
Volts (DC)	12
Ampere rating	70
Starter motor rated voltage (DC)	12
Battery, recommended cold cranking amps (CCA):	
Quantity, CCA rating	One, 640
Battery voltage (DC)	12

Fuel

Fuel System	
Fuel supply line, min. ID, mm (in.)	11.0 (0.44)
Fuel return line, min. ID, mm (in.)	6.0 (0.25)
Max. lift, engine-driven fuel pump, m (ft.)	3.0 (10.0)
Max. fuel flow, Lph (gph)	82 (21.7)
Fuel prime pump	Manual
Fuel filter	
Secondary	5 Microns @ 98% Efficiency
Water Separator	Yes
Recommended fuel	#2 Diesel

Lubrication

Lubricating System	
Type	Full Pressure
Oil pan capacity, L (qt.)	7.3 (7.7)
Oil pan capacity with filter, L (qt.)	8.2 (8.7)
Oil filter: quantity, type	1, Cartridge
Oil cooler	Water-Cooled

Application Data

Cooling

Radiator System

Ambient temperature, °C (°F)*	50 (122)
Engine jacket water capacity, L (gal.)	2.6 (0.7)
Radiator system capacity, including engine, L (gal.)	10.6 (2.8)
Engine jacket water flow, Lpm (gpm)	98 (26)
Heat rejected to cooling water at rated kW, dry exhaust, kW (Btu/min.)	35.7 (2030)
Heat rejected to air charge cooler at rated kW, dry exhaust, kW (Btu/min.)	10.9 (621)
Water pump type	Centrifugal
Fan diameter, including blades, mm (in.)	597 (23.5)
Fan, kWm (HP)	2.9 (3.9)
Max. restriction of cooling air, intake and discharge side of radiator, kPa (in. H ₂ O)	0.125 (0.5)

* Enclosure reduces ambient temperature capability by 5°C (9°F).

Operation Requirements

Air Requirements


Radiator-cooled cooling air, m ³ /min. (scfm)‡	96 (3400)
Combustion air, m ³ /min. (cfm)	4.3 (152)
Heat rejected to ambient air:	
Engine, kW (Btu/min.)	14.0 (747)
Alternator, kW (Btu/min.)	7.6 (435)

‡ Air density = 1.20 kg/m³ (0.075 lbm/ft³)

Fuel Consumption


Diesel, Lph (gph) at % load	Standby Rating	
100%	16.2	(4.3)
75%	12.1	(3.2)
50%	8.5	(2.2)
25%	5.0	(1.3)
Diesel, Lph (gph) at % load	Prime Rating	
100%	13.7	(3.6)
75%	10.8	(2.9)
50%	7.6	(2.0)
25%	4.5	(1.2)

Controllers



Decision-Maker® 550 Controller

Audiovisual annunciation with NFPA 110 Level 1 capability. Programmable microprocessor logic and digital display features. Alternator safeguard circuit protection. 12- or 24-volt engine electrical system capability. Remote start, remote annunciation, and remote communication options. Refer to G6-46 for additional controller features and accessories.



Decision-Maker® 3+, 16-Light Controller

Audiovisual annunciation with NFPA 110 Level 1 capability. Microprocessor logic, AC meters, and engine gauge features. 12- or 24-volt engine electrical system capability. Remote start, prime power, and remote annunciation options. Refer to G6-30 for additional controller features and accessories.

Additional Standard Features

- Alternator Protection (standard with 550 controller)
- Battery Rack and Cables
- Oil Drain and Coolant Drain w/Hose Barb
- Oil Drain Extension (with narrow skid and enclosure models only)
- Operation and Installation Literature
- Radiator Drain Extension (with enclosure only)

Available Options

Approvals and Listings

- ☐ CSA Approval
- ☐ IBC Seismic Certification
- ☐ UL2200 Listing

Enclosed Unit

- ☐ Sound Enclosure (with enclosed critical silencer)
- ☐ Weather Enclosure (with enclosed critical silencer)

Open Unit

- ☐ Exhaust Silencer, Critical (kit: PA-324470)
- ☐ Exhaust Silencer, Hospital (kit: GM32386-KP1)
- ☐ Flexible Exhaust Connector, Stainless Steel

Fuel System

- ☐ Auxiliary Fuel Pump
- ☐ Flexible Fuel Lines
- ☐ Fuel Pressure Gauge
- ☐ Subbase Fuel Tanks

Controller

- ☐ Common Failure Relay
- ☐ Communication Products and PC Software (550 controller only)
- ☐ Customer Connection
- ☐ Dry Contact (isolated alarm)
- ☐ Engine Prealarm Sender (16 light controller only)
- ☐ Prime Power Switch (550 controller only)
- ☐ Remote Annunciator Panel
- ☐ Remote Audiovisual Alarm Panel
- ☐ Remote Emergency Stop
- ☐ Remote Mounting Cable
- ☐ Run Relay

Cooling System

- ☐ Block Heater; Recommended for Ambient Temperatures Below 0°C (32°F)
- ☐ Radiator Duct Flange

Electrical System

- ☐ Alternator Strip Heater
- ☐ Battery
- ☐ Battery Charger, Equalize/Float Type
- ☐ Battery Heater
- ☐ Line Circuit Breaker (NEMA type 1 enclosure)
- ☐ Line Circuit Breaker with Shunt Trip (NEMA type 1 enclosure)
- ☐ Safeguard Breaker (not available with 550 controller)

Paralleling System

- ☐ Reactive Droop Compensator
- ☐ Remote Speed Adjust Control/Electronic Governor
- ☐ Voltage Adjust Control
- ☐ Voltage Regulator Relocation

Miscellaneous

- ☐ Air Cleaner, Heavy Duty
- ☐ Air Cleaner Restriction Indicator
- ☐ Closed Crankcase Vent
- ☐ Engine Fluids (oil and coolant) Added
- ☐ Rated Power Factor Testing
- ☐ Rodent Guards
- ☐ Skid End Caps

Literature

- ☐ General Maintenance
- ☐ NFPA 110
- ☐ Overhaul
- ☐ Production

Warranty


- ☐ 2-Year Basic
- ☐ 2-Year Prime
- ☐ 5-Year Basic
- ☐ 5-Year Comprehensive
- ☐ 10-Year Major Components

Other Options

- ☐ _____
- ☐ _____

Dimensions and Weights

Overall Size, L x W x H, mm (in.):
 Wide Skid: 2300 x 1040 x 1133 (90.55 x 40.94 x 44.61)
 Narrow Skid: 1998 x 780 x 1067 (78.66 x 30.71 x 42.01)
 Weight (radiator model), wet, kg (lb.): 755 (1665)



NOTE: This drawing is provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.

DISTRIBUTED BY: